

FEMALE SIZING FORM

Email completed form to customercare.psp@safariland.com or fax to (888) 969-5469

DATE: _____



SHIP-TO INFORMATION

NAME: _____

ADDRESS: _____

CITY: _____ PROV: _____ POSTAL CODE: _____

PHONE: _____ EMAIL: _____

OPTIONS

SUSPENDERS ☐
(please select to receive suspenders)

CHOOSE ONE ☐

STRUCTURED FEMALE

OR

GENDER NEUTRAL FEMALE ☐

SIZING INFORMATION


OFFICER NAME: _____ HEIGHT: _____ WEIGHT: _____ CUP SIZE: _____

AGENCY: _____ BADGE #: _____ SIZED BY: _____

MEASURE OFFICER IN FULL UNIFORM AND DUTY BELT. USE CLOTH MEASURING TAPE. COMPLETE ALL FIELDS.
MEASURE TO THE NEAREST INCH. ROUND UP (LONGER) ON WAIST/CHEST. ROUND DOWN (SHORTER) ON LENGTHS.

A

BAND MEASUREMENT




Measure circumference of upper chest, under the armpit. Tape should be level around entire chest. Round up to nearest inch.

_____ in.

B

BUST MEASUREMENT




Measure bust circumference at widest point. Tape should be level around entire bust. Round up to nearest inch.

_____ in.

C

UNDER BUST MEASUREMENT




Measure torso circumference at widest point under bust. Tape should be level around entire torso. Round up to nearest inch.

_____ in.

D

WAIST MEASUREMENT



B1. Measure circumference at widest point of abdomen. Tape should be level around entire torso. Round up to nearest inch.

_____ in.

Waist measurements are used to determine front and back panel widths. Reference Overlap Calculation Chart and select desired overlap.


Overlap Calculation Chart	Butt Fit	
_____	1" Overlap	add 2" to waist measurement
_____	2" Overlap	add 4" to waist measurement
_____	2" Overlap	add 6" to waist measurement

B2. Select front/back panel widths below that most closely add up to total waist. Front panel must be as wide or wider than

Front Panel Width	16	18	20	22	24	26	28	30	32	34
Back Panel Width	16	18	20	22	24	26	28	30	32	34

E

FRONT SEATED MEASUREMENT




Measure length from clavicle notch down to top of duty belt, while seated. Officer should be at a relaxed, 90° position. Tape should lie unassisted against officer's body. Do not follow contour of body. Subtract 1" from measurement. Round down to nearest inch.

FRONT _____ - 1" = _____ in.

F

BACK STANDING MEASUREMENT



Measure length from nape (back neck bone) down to top of duty belt, while standing. Round down to nearest inch. Front/back measurements should be no more than 2" apart.

BACK _____ - 1" = _____ in.

1

FRONT PANEL WIDTH
Measurement B2 Front

2

FRONT PANEL LENGTH
Measurement C

3

BACK PANEL WIDTH
Measurement B2 Back

4

BACK PANEL LENGTH
Measurement D